



IP20

RoHS
compliant

REACH
COMPLIANCE

Made in
Germany

CE

UK
CA

UL
in progress

Specifikationer

IP-Klass (EN 60529)	IP20
Material	Polyamid
Brandklass	
Temperatur	-20 C° till 50 C°
Monteringstyp	Skruvmontering

Fördelar

Produkttyper och storlekar



ArtNr.	81132	Connector	C8 connector
EAN	4251269333071	type	
Antal	1	Rated current	2,5 A
Längd	85,2 mm	Protection	II (Protective insulation)
Höjd	24 mm	class	
Bredd	63,2 mm	Färg	svart
Length connecting cable	600 mm		



ArtNr.	81232	Length connecting cable	600 mm
EAN			
Antal	1	Connector type	C8 connector
UL-certifikat	cURus (in progress)	Rated current	2,5 A
Längd	85,2 mm	Protection class	II (Protective insulation)
Höjd	24 mm	Färg	svart
Bredd	63,2 mm		



ArtNr.	81334	Connector type	C8 connector, angled
EAN	4251269333002	Rated current	2,5 A
Antal	1	Protection class	II (Protective insulation)
Längd	85,2 mm	Färg	svart
Höjd	24 mm		
Bredd	63,2 mm		
Length connecting cable	600 mm		

ArtNr.	81133	Connector	C8 connector
EAN	4251269333	type	
	088	Rated current	2,5 A
Antal	1	Protection	II (Protective insulation)
Längd	85,2 mm	class	
Höjd	24 mm	Färg	svart
Bredd	63,2 mm		
Length connecting cable	1.500 mm		



ArtNr.	81233	Length connecting cable	1.500 mm
EAN			
Antal	1	Connector type	C8 connector
UL-certifikat	cURus (in progress)	Rated current	2,5 A
Längd	85,2 mm	Protection	II (Protective insulation)
Höjd	24 mm	class	
Bredd	63,2 mm	Färg	svart





ArtNr.	81333	Connector	C8
EAN	4251269332	type	connector,
	999		angled
Antal	1	Rated current	2,5 A
Längd	85,2 mm	Protection	II (Protective
Höjd	24 mm	class	insulation)
Bredd	63,2 mm	Färg	svart
Length connecting cable	1.500 mm		

icotek[®]
smart cable management